



KITSILANO DEEP TEXTURED LACQUERED PANELS CARE AND CLEANING INSTRUCTIONS —————

Cleaning

Use a soft cloth and a mild soapy water solution to remove dirt and grease. Rinse immediately with a clean cloth and dry with a clean soft cloth, using light pressure. Avoid vigorous rubbing, as this tends to raise glossy spots, marring the original effect. Never use strong soaps, detergents or liquid wax cleaners with dirt cutting agents on wood finishes.

Avoid harsh household cleaners and abrasives. The following cleaning agents should not be used under any circumstances:

- Scouring and abrasive agents (abrasive powders, scouring pads, steel wool)
- Polish, washing powder, furniture cleaner, bleach
- Detergents with strong acids and acidic salts
- Steam cleaning equipment

Always check the active ingredients of your cleaners for potentially harmful chemicals. Do not use acetone, ammonia, amylacetate, benzene, butylacetate, butyl alcohol, caustic soda, cellusolve, chlorinated solvents, chloroform, cresols/phenols, dichloromethane, ethylacetate, glacial acetate acid, halogenated solvents, methyl alcohol, methyl ethyl ketone, thinners, toluene, or xylene.

Keep cabinet surfaces dry and free from standing liquids.

If chemical or staining liquids are spilled on the lacquered surface, wipe it off immediately and wash the surface with soapy water, rinsing several times to eliminate any residue.